



# BARGE: DBL 255

## INNAGE TRIM TABLE

	1 FT.		2 FT.		3 FT.		4 FT.		5 FT.		6 FT.	
	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>
1 CENTER	00-1/2	- 00-1/2	01-0/8	- 01-0/8	01-1/2	- 01-1/2	02-0/8	- 02-0/8	02-1/2	- 02-1/2	03-0/8	- 03-0/8
2 CENTER	- 00-3/8	00-3/8	- 00-5/8	00-5/8	- 01-0/8	01-0/8	- 01-1/4	01-1/4	- 01-5/8	01-5/8	- 02-0/8	02-0/8
3 CENTER	00-1/8	- 00-1/8	00-1/8	- 00-1/8	00-1/4	- 00-1/4	00-3/8	- 00-3/8	00-1/2	- 00-1/2	00-1/2	- 00-1/2

(ALL MEASUREMENTS ABOVE ARE IN INCHES)

EXAMPLE FOR ABOVE TRIM CORRECTIONS:

FWD. DRAFT = 2'-00"  
 AFT DRAFT = 4'-00"  
 DIFF. = 2'-00" (DOWN BY STERN)

LENGTH BETWEEN DRAFT MARKS: 147'-03"

February 13, 2019

THE CORRECTION FOR 2'-00" TRIM DOWN BY STERN FOR 1 CENTER IS - 01-0/8"  
 FOR A MEASURED INNAGE GAUGE OF 4'-00" ON 1 CENTER, THE TRIM CORRECTED INNAGE IS 3'-11"











